

Characteristics

- NXP i.MX 6 ARM Cortex®-A9 with up to 1GHz
- up to 512MB SLC NAND Flash, 32GB eMMC, 2GB RAM
- RGB, 2-Channel TFT LVDS
- DVI Interface
- Ethernet 10/ 100/ 1000MBit
- 1x USB2.0 Device/ Host, 1x USB2.0 Host
- 2x CAN2.0, 2x I²C, 2x SPI
- 2x SD-Card
- 1x I2S Audio
- 1x PCIexpress (2.0)
- 1x SATA (Quad-Core)
- Digital Camera Interface (optional)
- Windows Embedded Compact 7/2013, Linux
- 5V Design




Description

efus™ A9 is a compact and inexpensive module in efus™ form factor. It is perfectly suited for applications with numerous interfaces in the medical and industrial sector. Along with its easy baseboard (EasyLayout), efus™ (47 x 62mm only) also fits in small housings.

The i.MX 6 Cortex®-A9 CPU has high processing power and excellent multimedia features (3D graphics, 1080p Decoder, H.264 HP, ARMv7, NEON and VFPv3). NXP's chip design sets special focus on scalability. Other special characteristics are the long-time availability of up to 15 years and a temperature range of up to -20°C - +85°C.

The module provides numerous interfaces like USB Host/Device, CAN, UART, I²C, SPI, I²C Audio, Touch Panel, digital Camera, PCIe and SATA. efus™ A9 also has interfaces for RGB, 2x LVDS and DVI.

Block Diagram



On-Board Operating System



The customized WEC 7/2013 (bootloader, kernel, interface drivers, Silverlight, Mediaplayer, IE) is a powerful real-time operating system.

Along with .NET and XAML it is the ideal base for software development.



The F&S Linux BSP (4.1.x, uboot, Buildroot, Yocto, QT, GStreamer) contains the customized kernel with all interface drivers, including source.

A Cross Compiler Toolchain for the creation of own bootloaders, kernels and further software is available.

Starterkit

The efus™ A9 starterkit consists of a base board with standard connectors and pin headers for the offered interfaces.

It also includes a cable kit, access data to download documentations, current software, drivers and example programs.

The starterkit is available with or without display kit.

For an easy start of development, we offer a four-hour workshop.

Aim is to get an introduction to the efus™ A9 starterkit and the development environment. You will be able to start your own development with a running system (efus™ A9, display and touch panel).

Our support forum with more than 3000 registered customers is always online for help.

efus™ stands for 20 years of experience in the RISC boards sector.

easy

starterkits
customized operating systems
(Linux, WEC 7/2013)
F&S Support, free of charge

functional


many interfaces
easy base board
based on "EasyLayout" standard

universal

visualization
communication
control

small

47 x 62mm only
5V supply



Accessories

Fail-safe Flash Filesystem (F3S)

Order no. WCE-F3S

Offers transaction safety on file level and therefore guarantees the consistency of the data, even in case of a blackout or other interferences while writing.

Displaykit RGB

Order no. aSt-RGBKIT

7" WVGA display with RGB interface and touch panel, connection cable (40poles film cable), display adapter and touch cable

Workshop

Order no. NDCU-WS1

Four-hour workshop at F&S in Stuttgart. Our workshop will help you start working with Windows CE/ Linux and the F&S products easier.

Technical Data

| | |
|--------------------|--|
| Power Supply: | +5V _{DC} / ±5% |
| Power Consumption: | 3W typ. |
| Interfaces: | 1x Ethernet 10/ 100/ 1000 MBit 4x Serial 1x USB2.0 Host 1x USB2.0 Device/ Host 2x CAN2.0 2x I ² C 2x SPI 1x I2S Audio 1x SATA PCIe (2.0) Camera Interface |
| TFT LCD-Interface: | 18Bit RGB up to XGA 2x 24bit LVDS up to FullHD DVI up to FullHD |
| RAM: | up to 2GB RAM |
| Program Memory: | up to 512MB SLC NAND Flash, up to 32GB eMMC |
| Processor: | ARM Cortex® A9 Solo/ DualLite/ Quad-Core 1GHz |
| Temperature Range: | 0°C - +70°C , (-20°C - +85°C optional) |
| Size: | 47mm x 62.1mm x 11mm (l x b x h) |
| Weight: | 15g |

Standard Versions / Order Notations

efusA9-V2-LIN

Solo-1GHz, 512MB RAM, 256MB Flash, RGB, LVDS, DVI, Linux

efusA9-V2-WEC7

Solo-1GHz, 512MB RAM, 256MB Flash, RGB, LVDS, DVI, WEC 7

efusA9-V2-W13

Solo-1GHz, 512MB RAM, 256MB Flash, RGB, LVDS, DVI, WEC 2013

efusA9-V3-LIN

DualLite - 1GHz, 512MB RAM, 256MB Flash + 2GB eMMC, RGB, LVDS, DVI, Linux

efusA9-V3-WEC7

DualLite - 1GHz, 512MB RAM, 256MB Flash + 2GB eMMC, RGB, LVDS, DVI, WEC 7

efusA9-V3-W13

DualLite - 1GHz, 512MB RAM, 256MB Flash + 2GB eMMC, RGB, LVDS, DVI, WEC 2013

efusA9-V3-LIN

DualLite - 1GHz, 512MB RAM, 256MB Flash + 4GB eMMC, RGB, LVDS, DVI, -20°C +85°C, Linux

efusA9-V3-W13

DualLite - 1GHz, 512MB RAM, 256MB Flash + 4GB eMMC, RGB, LVDS, DVI, -20°C +85°C, WEC2013

efusA9-V3-1D-LIN

DualLite - 1GHz, 1GB RAM, 256MB Flash + 4GB eMMC, RGB, LVDS, DVI, -20°C +85°C, Linux

Standard Versions / Order Notations

efusA9-SKIT-LIN/ W13

efusA9-V3-LIN or -W13, base board, cable kit, display kit, access to documentation and software

efusA9-SKIT2-LIN/ W13

efusA9-V2-LIN or -W13, base board, cable kit, access to documentation and software

Custom versions possible, MOQ 500pcs

