

EC AXIAL FAN COMES WITH SEVERAL ADVANTAGES COMPARED WITH CONVENTIONAL AC AXIAL FANS

More than 60 %
energy saving

Applicable
for ErP2015

Higher efficiency with
more air flow

Selectable
Customized speed

IP55 / IP68 / ATEX is
available for choice



APPLICATIONS

- Commercial refrigerator
- Freezer
- Icemaker
- Vending machine
- Air-conditioning

UF-T12ABPB0AM1D4A



MODEL NO.

DIMENSION

RATED VOLTAGE

OPERATING VOLTAGE

POWER

SPEED

AIR FLOW

PRESSURE

NOISE

AVAILABLE MODULES

UF-T200BMB11M1D4A	Ψ 250 x 76.1 mm	115 VAC	103 to 126 VAC	8.1 W	1400 RPM	290 CFM	0.28 InchH ₂ O	44 dB
	Ψ 250 x 76.1 mm	115 VAC	103 to 126 VAC	26.0 W	2200 RPM	460 CFM	0.46 InchH ₂ O	55 dB
UF-T200BMB23M1D4A	Ψ 250 x 76.1 mm	230 VAC	207 to 253 VAC	8.5 W	1400 RPM	290 CFM	0.28 InchH ₂ O	44 dB
	Ψ 250 x 76.1 mm	230 VAC	207 to 253 VAC	27.0 W	2200 RPM	460 CFM	0.46 InchH ₂ O	55 dB
UF-T15PBP23M1D4A	Ψ 172 x 150 x 51 mm	230 VAC	207 to 253 VAC	15.0 W	3000 RPM	220 CFM	0.62 InchH ₂ O	54 dB
UF-T15PBPB11M1D4A	Ψ 172 x 150 x 51 mm	115 VAC	207 to 253 VAC	15.0 W	3000 RPM	220 CFM	0.62 InchH ₂ O	54 dB
UF-T60BBPB0AM1D4A	Ψ 60 x 60 x 25 mm	115 VAC	95 to 264 VAC	2.0 W	3850 RPM	18.7 CFM	0.172 InchH ₂ O	31 dB
	Ψ 60 x 60 x 25 mm	230 VAC	95 to 264 VAC	2.3 W	3950 RPM	19.4 CFM	0.178 InchH ₂ O	31 dB
UF-T12ABPB0AM1D4A	Ψ 120 x 120 x 38 mm	115 VAC	95 to 264 VAC	4.9 W	3200 RPM	106 CFM	0.34 InchH ₂ O	43 dB
	Ψ 120 x 120 x 38 mm	230 VAC	95 to 264 VAC	5.2 W	3200 RPM	106 CFM	0.34 InchH ₂ O	43 dB